



K 250

CLASSIC · EXTRA

TSR

SELF-PRIMING PUMPS



MODELO:
K 250 10/150 Classic

ARTÍCULO:
C2582AR

MODELO:
K 250 TSR 13/190 T Classic

ARTÍCULO:
C2583AR



Ergonomic handle for easy maneuverability

Empuñadura ergonómica para mayor practicidad de maniobra y transporte



ON CLASSIC VERSIONS

Without hose reel at the top

EN VERSIÓN CLÁSICA

Sin carrete para manguera.



LW-K250

Pump with 3 integral ceramic pistons. Oil sight glass. Brass pump heads

Bomba con 3 pistones cerámicos. Visor de nivel de aceite. Tapa en bronce.



Removable detergent tank with externally visible level

Depósito de detergente fácilmente removible, y con indicador de nivel



Can be used vertically or horizontally

Utilizable en vertical y en horizontal



FOR MORE INFO:
MAGGIOR INFORMAZIONI:



GENERAL FEATURES · CARACTERÍSTICAS GENERALES

- Sturdy injection-moulded plastic casing
- Handy lance and gun storage
- Handle with supports for the power cable and delivery hose
- Easy maintenance by simply removing the front casing
- Big wheels (Ø 210mm) for easy movement up and down steps and over uneven ground
- Removable detergent tank with level visible from the outside
- Regulated low-pressure detergent suction with filter
- Pressure gauge
- 4-pole motor (1400 rpm) well oversized and protected with paint
- Built-in professional unloader valve
- Delayed Total Stop
- **Self-priming** pumps with EASY START device on single-phase models
- Rotary switch
- Motor thermal protection
- Robusto carenado en material plástico inyectado
- Práctico alojamiento de pistola y lanza
- Empuñadura con soporte de cable y manguera
- Fácil acceso para mantenimiento: Acceso a todas sus partes al quitar tapa frontal.
- Ruedas de 200 mm para facilitar la rodadura en cualquier superficie y/o terrenos accidentados.
- Recipiente de detergente con visor de nivel
- Aspiración de detergente en baja presión, con filtro incorporado.
- Manómetro
- Motor trifásico de 1400 RPM sobredimensionado y protegido con barniz.
- Válvula de regulación profesional integrada
- "Total-Stop" Temporizado
- Bomba auto-cebante con EASY-START en modelo monofásico
- Interruptor rotativo
- Motor con protector térmico
- Uso profesional

TECHNICAL FEATURES · CARACTERÍSTICAS TÉCNICAS

CODE CÓDIGO	MODELS MODELO	PUMP BOMBA																			
			Ph	V	Hz	bar	MPa	bar	MPa	l/h	HP	kW	kW	lt	kg	(L x W x H) cm					
9057 0102	K250 10/150 M Cl.	LW-K250	1	230	50	150	15	30÷135	3÷13,5	280÷600	3,0	2,2	2,9	3,5	40	54 x 44 x 68					
9057 0101	K250 10/150 M Ex.	LW-K250	1	230	50	150	15	30÷135	3÷13,5	280÷600	3,0	2,2	2,9	3,5	40	54 x 44 x 68					
9057 0104	K250 12/130 M Cl.	LW-K250	1	230	50	130	13	30÷115	3÷11,5	360÷720	3,0	2,2	2,9	3,5	40	54 x 44 x 68					
9057 0103	K250 12/130 M Ex.	LW-K250	1	230	50	130	13	30÷115	3÷11,5	360÷720	3,0	2,2	2,9	3,5	50	54 x 44 x 68					
9057 0106	● K250 11/160 M Cl.	LW-K250	1	230	50	160	16	30÷145	3÷14,5	300÷660	3,5	2,6	3,3	3,5	40	54 x 44 x 68					
9057 0105	● K250 11/160 M Ex.	LW-K250	1	230	50	160	16	30÷145	3÷14,5	300÷660	3,5	2,6	3,3	3,5	50	54 x 44 x 68					
9057 0108	K250 13/190 T Cl.	LW-K250	3	400	50	190	19	30÷180	3÷18	330÷780	5,5	4,0	5,0	3,5	40	54 x 44 x 68					
9057 0107	K250 13/190 T Ex.	LW-K250	3	400	50	190	19	30÷180	3÷18	320÷780	5,5	4,0	5,0	3,5	50	54 x 44 x 68					
9057 0110	K250 15/170 T Cl.	LW-K250	3	400	50	170	17	30÷160	3÷16	300÷900	5,5	4,0	5,0	3,5	40	54 x 44 x 68					
9057 0109	K250 15/170 T Ex.	LW-K250	3	400	50	170	17	30÷160	3÷16	390÷900	5,5	4,0	5,0	3,5	50	54 x 44 x 68					
9057 0112	K250 11/210 T Cl.	LW-K250	3	400	50	210	21	30÷200	3÷20	260÷660	5,5	4,0	5,0	3,5	40	54 x 44 x 68					
9057 0111	K250 11/210 T Ex.	LW-K250	3	400	50	210	21	30÷200	3÷20	260÷660	5,5	4,0	5,0	3,5	50	54 x 44 x 68					

● Requires 4kW single-phase electricity supply · Requiere red eléctrica monofásica con capacidad de 4 kW

STANDARD EQUIPMENT · EQUIPAMIENTO STANDARD

<p>CLASSIC</p> <p>GC251 gun with protection Pistola GC251 con protección</p>	<p>EXTRA</p> <p>GH281 gun with Swivel and pressure regulator Pistola GH281 con regulación giratoria de presión</p>	<p>CLASSIC EXTRA</p> <p>Bent lance with detergent head Lanza curva de acero inoxidable con tobera para detergente</p>	<p>EXTRA</p> <p>Lance with rotating nozzle Lanza recta con salida rotante</p>
<p>CLASSIC</p> <p>10 m rubber delivery hose kit Manguera de 10m de longitud</p>	<p>EXTRA</p> <p>15 m rubber delivery hose kit (on Hose Reel) Carrete con manguera de 15m de longitud</p>	<p>CLASSIC EXTRA</p> <p>15° spray nozzle, 1/4" MEG connection Boquilla abanico 15°; 1/4" MEG</p>	